



thermal protection perfection

The unique Tempro® adjustable cover extends in height from 900mm to 1800mm and is ideal for part reducing or varying pallet loads. It folds flat when not in use.

This cover is outstanding at keeping chilled or frozen goods in their own environment for extended periods in alien conditions.

It increases payloads, provides economic mixed loads and improves delivery turnaround time.

Achieves temperatures never previously considered possible.

As the load diminishes the cover height can be adjusted, increasing the thermal protection for remaining product.

- **Tempro® covers save time by-passing cold rooms and reduce labour and transport costs by 60%.**
- **Palletise goods will be temperature protected.**
- **Tempro® covers enable mixed temperature loads on any vehicle to provide significant cost savings.**
- **Tempro® covers offer outstanding Thermal protection in aliens conditions.**
- **Tempro® covers can be height adjusted using Velcro to suit the load.**
- **1200mm by 1000mm by 1800mm high for UK pallets and 800mm by 1200mm by 1800mm high for Euro pallets are available ex stock.**
- **Working lives of covers can be extended by repair or the covers can be recycled.**

Tempro® Adjustable Pallet Covers

“Adjusts to your Thermal Needs”



Thermal Information

Below is a table showing the results attained by Campden BRI during testing:

Product	Thermal Resistance			Thermal Transmittance
	Tog	Clo	K Value m ² K/W	U Value W/(m ² K)
TF25 Temprow [®] 25mm Standard	6.6	4.26	0.66	1.52
TF12 Temprow [®] 12mm Light Duty	5.4	3.48	0.54	1.85

Figures may be improved when Temprow[®] is matched with different face or lining materials or if a heavier Temprow[®] core specification is demanded.

Temprow[®] Technical information and trial results available.

Technical Specification;

External material is Blue PU Nylon and White PU Nylon internally.

Insulation grade is TF25 Standard Temprow[®] with an intrinsic thermal resistance of 0.66m²K/W.

Temprow[®] is Fire Retardant to BS 5867: Pt 2 1980.



Typical Users and Uses of Temprow[®]

Supermarket groups	Food Processors	Veterinary products	Chemicals
Warehouses	Cash and Carry's	Mixed distribution systems	MOD
Dairy Produce	Fish Wholesalers	Delicatessen	Restaurants
Pharmaceuticals	Transportation of vaccines	Manufacturing Deliveries	Caterers
Grocery Distribution	Transportation of blood	Transport Companies	Bakeries



Contact details are as follows:
Seymour Manufacturing International Ltd
 Unit 3, Stafford Park 16, Telford, Shropshire,
 TF3 3BS

Tel: +44 (0) 1952 201 201 Fax: +44 (0) 1952 201 200
 email: enquiries@seymour-mi.com
 Website: www.seymour-mi.com

SCAN ME

